

Stock Flush Door & Frame Program

3070 Single Door & Frame, 6070 Pair Doors & Frame, Door Only or Frame Only (Flush Door Only)

- **Lead-Time (4) Working Days** following receipt of PO and all necessary information.
An order Received by Noon CST Monday will ship that Friday (Holiday weeks Excluded).
- **Maximum Quantity (3) Door Leaves and/or (3) Frames. No Order Splitting.**
- **Standardized Unit Pricing (Plus Freight).**
- **PO Must Clearly Indicate “STOCK PROGRAM”, Handing, Color and All Options.**

Color: WHITE, BEIGE, STD GRAY or BLUE matte polyurethane finish or Primed Only (field paint by others).

Flush FRP Door: Smooth Face – Foam (Urethane) Core

- Net Size 35-13/16” x 83-1/8” - Surface Closer Blocking
- Active Door (Single/Pair) Beveled Lock Edge (1/8”/2”)
- Active Door (Single/Pair) 18” Surface Panic/Push/Pull Blocking at 41-3/8” TTCL(42-1/2” AFF)
- In-Active Door (Pair) Square Strike Edge - 10” Surface Bolt Blocking Top & Bottom
- (3) 4-1/2” Std Wt (.134) Hinge Preps (STD = TTT 5-1/8”, 37-1/8”, 69-1/8”, ¼” BS)
Option: Non-standard locations – Advise TTT’s & BS.
- **Option: Active (Single/Pair) Latchset Prep**
(C) 161 Cylindrical Lock (STD = 43-9/16” TTCL)
(DL) 161 Cylindrical Deadlock (STD = 35-7/8” TTCL)
(MNF) Mortise Pocket Only, No Function Holes (STD = 43-15/16” TTCL)
Option: Non-standard Latchset Location(s) – Advise TTCL(s).
- **Option: In-Active of Pair Prep**
(STK) 4-7/8” ASA Strike (STD = 43-9/16” TTCL)
(DLSTK) 2-3/4” LL Strike (STD = 35-7/8” TTCL)
(FB) Flushbolt (ANSI 115.4; 12” extension) Top and Bottom
Option: Non-standard Strike Location(s) – Advise TTCL(s).

FRP Frame: KD Standard Profile 5-3/4” x 2”

- (6) Concealed SS Existing Masonry Anchors (w/1” Dia Color Matched Cap)
- Surface Closer Blocking
- (3) 4-1/2” Std Wt (.134) Hinge Preps (STD = TTT 5-1/4”, 37-1/4”, 69-1/4”, 5/16” BS)
Option: Non-standard locations – Advise TTT’s & BS.
- **Option: 4” Header**
- **Option: Strike Prep**
(STK) 4-7/8” ASA Strike (STD = 43-11/16” TTCL)
(DLSTK) 2-3/4” LL Strike (STD = 36” TTCL)
(FBSTK) Flushbolt Strike ANSI 115.4
Option: Non-standard Strike Location(s) – Advise TTCL(s).