



Corrosion Immune Fiberglass Doors & Frames

**AMERICA'S PREMIER INDUSTRIAL FIBERGLASS DOOR AND FRAME SYSTEM  
WILL NEVER RUST — GUARANTEED — EVEN IN HIGHLY CORROSIVE ENVIRONMENTS**

**SERVING THE INTERNATIONAL ARCHITECTURAL / CONSTRUCTION INDUSTRY FOR OVER 30 YEARS**

- Lifetime warranty against corrosion
- Urethane foam, end grain balsa, honeycomb or mineral core available
- Smooth or pebble face sheets available
- Polyurethane, prime or gelcoat finish available
- Completely sealed against the elements
- Chemical and salt resistant
- Beveled lock edge on active leaves
- Wide range of frames and hardware preps
- Unlimited design and application capabilities
- Tough, abuse resistant - passed 1 million cycle slam test
- Impervious to moisture, gasses and bacteria
- Ideal where FDA/USDA/OSHA regulations must be considered



UL approved 20 to 90 minute positive pressure FRP doors and FRP frames



Florida Building Code Approved Including HVHZ

**SPECIFICALLY DESIGNED FOR:**

- |                              |                        |                              |
|------------------------------|------------------------|------------------------------|
| Animal Shelters              | Offshore Platforms     | Veterinary Facilities        |
| Car Washes / Marinas         | Pharmaceuticals        | Waste Water Treatment Plants |
| Chemical Plants / Refineries | Pools / Chlorine Rooms | Water Parks / Showers        |
| Clean Rooms                  | Pulp / Paper Mills     | Water Treatment Plants       |
| Detention Facilities         | Schools                | YMCA's                       |
| Food Processing              | Sports Facilities      | Zoos / Aquariums             |
| Hospitals                    | Utilities              |                              |



**CORRIM**


Distributed By:

1870 Stillman Drive Oshkosh, WI 54901-1010  
Phone: 920-231-2000 • Fax: 920-231-2238  
www.corrim.com • info@corrim.com


# CORRIM FIBERGLASS (FRP)

## DOORS

### TYPICAL DOOR CONFIGURATIONS




## FRAMES




Standard Frames

## MODIFIED FRAMES




Contact factory for special frame depth sizes.

### TYPICAL CONSTRUCTION DETAIL




### TYPICAL FRAME GLAZING OPTIONS



Standard Glazing (standard)

### TYPICAL DOOR GLAZING OPTIONS




Single Glazing (standard)

Rabbetted Single Glazing (optional)

Sanitary Single Glazing SS MVF (optional)

### FIXED WALL LOUVER





In accordance with a continuing program of product research and development, CORRIM reserves the right to change design and/or details of its products without notice.

# UL APPROVED FRP DOORS AND FRP FRAMES



When a fire rating must be combined with corrosion resistance and security - Corrim fire doors and frames are ideal. The solid mineral core door, combined with structural FRP stiles and rails is totally sealed and impervious to the invasion of moisture, gases and bacteria.

Corrim's UL labeled FRP frames have the same strong, pultruded profile as our non-rated frames. Our light weight, hollow back frame does not require backfilling with grout — making installation a breeze. Multiple anchor options are available. As with all of Corrim's FRP products, our fire rated doors and frames come with a lifetime warranty against corrosion.




- 20, 30, 45, 60 and 90 minute UL labels
- Passed ANSI/UL 1-1/2 hour fire, hose stream and positive, neutral/negative pressure tests
- Self-sealing against flames, smoke and fumes
- Passed the 250° temperature rise rating
- Singles up to 4-0 x 8-0
- Pairs up to 8-0 x 8-0
- Passed the slam and durability test per ANSI A151.1
- FBC (Florida Building Code) approved for single openings
- Intumescent seal applied to frame

## AVAILABLE ANCHORS FOR UL LABELED FRP FRAMES



## GLAZING DETAILS FOR UL LABELED FRP DOORS


Metal Vision Frame with Fire Rated Glass




- Lites up to 100 square inches for 60 and 90 minute doors (larger sizes available with temperature rise rated glazing)
- Lites up to 1296 square inches for 30 and 45 minute doors
- Louver up to 24" x 24" with Fusible Link, non temperature rise only

## ASTRAGAL OPTIONS FOR 90 MINUTE RATED PAIRS


Metal Astragal Required On 90 Minute Pairs With A Lock And Flushbolt Or Surface Bolts And Surface Vertical Rod/Mortise Exit Devices.




Metal Edges Required On 90 Minute Pairs With A Surface Vertical Rod/Surface Vertical Rod Devices



## STANDARD COLORS



Polyurethane  
Primer\*



WG-7000  
White



NG-74306  
Beige




AG-7505  
Standard Gray



LG-7053  
Blue

**\* PRIME FINISH RECOMMENDED FOR NEW CONSTRUCTION**

## OPTIONAL COLORS



UG-7160  
Light Yellow



LG-70917  
Light Blue



GG-70618  
Aqua




LG-70097  
Royal Blue




TG-7300  
Santa Fe Tan



YG-70064  
Burnt Orange



NG-7501  
Antique Brown



NG-99999  
Dark Brown



GG-70059  
Green



GG-70907  
Forest Green



RG-70666  
Brick Red



MG-70009  
Burgundy



AG-72119  
Light Gray



AG-71275  
Medium Gray



AG-7552  
Dark Gray



NG-74103  
Dark Bronze



RE-7074  
Safety Red



YG-70672  
Safety Orange



UG-7011  
Yellow



GG-71354  
Safety Green

FINISH	SMOOTH FACESHEET	PEBBLE FACESHEET
Polyurethane Flat	Optional	N/A
Polyurethane Semi - Gloss	<b>Standard</b>	<b>Standard</b>
Polyurethane Gloss	Optional	Optional
Gel Coat Matte	Optional	N/A

Custom color matching is available. Corrim prefers to match with RAL color numbers

**All colors shown have been matched within limits of reproduction methods and actual color may vary.**

[www.corrim.com](http://www.corrim.com)